

Solenoid Valves for Cooling Towers



Parker Jackes-Evans GP Series Solenoid Valves Normally Closed

For Various Applications Including:

- Car Washes
- Commercial Dishwashers
- Hydronic Applications
- Competitive Pricing
- Highest Quality Components
- Replaces ASCO

AIR, WATER, OIL

Maximum Temp. 225°F / 107°C

Model No.	Part No.	Port Size	Cv	Connections	PSI
GP300	70392	1/2"	3.35	3/8" FPT	1-150
GP400	70562	1/2"	3.35	1/2" FPT	1-150
GP600	70712	3/4"	7.40	3/4" FPT	1-150
GP10A	70810	1"	12.20	1" FPT	1-150

STEAM

Maximum Temp. 300°F / 149°C

Model No.	Part No.	Port Size	Cv	Connections	PSI
GP357	70394	1/2"	3.35	3/8" FPT	1-50
GP457	70564	1/2"	3.35	1/2" FPT	1-50
GP657	70714	3/4"	7.40	3/4" FPT	1-50
GP1057	70777	1"	12.20	1" FPT	1-50



GP400

GP Series Solenoid Coils (Sold Separately)

G23 COILS

Class "F" Molded

Model No.	Part No.	Watts	Volts*	Hz	VA Holding	VA Inrush
G23-24V	77300	9	24 VAC	50/60	12	30
G23-120/240	77360	9	120/240 VAC	50/60	12	30

*G23 coils are available in 12, 24, 120, 208/240, 480, 120/240 VAC and also 12 and 24 VDC. Constructed in accordance with UL, IEEE, and NEMA.



G23 Coil



GLENGARRY Chemicals Ltd.
33 Melford Drive, Unit #6
Scarborough, Ontario, M1B 2G6
Telephone 416-757-1333
Fax 416-757-9793
glengarrychemicals1@on.aibn.com

