

## **OXVOID L STEAM BOILER TREATMENT**

### **DESCRIPTION**

Oxvoid L Steam Boiler Treatment is an oxygen scavenger, which will quickly and effectively react with dissolved oxygen in the feedwater and boiler water to prevent oxygen pitting in the boiler.

Oxvoid L is approved for used in federally registered food establishments. Oxvoid L should be used along with other scale inhibiting boiler water treatments.

Oxvoid L is concentrated liquid product with a clear brown appearance and the following characteristics:

pH:	9.0 to 10.0
S.G.:	1.10 to 1.20

### **APPLICATION**

In systems with deaerating heaters, it is preferable to feed Oxvoid L directly to the storage section of the heater. Alternatively Oxvoid L can be used with other boiler treatments and be fed directly to the condensate tank, fed into the boiler feed line with a bypass feeder or injected into the system with a positive displacement chemical pump. For the best feeding procedure, consult with your Glengarry Service Representative.

The dosage of Oxvoid L is dependent on the operating condition of the boiler and should be fed to maintain a sulphite residual 40 to 50 ppm. Exposure to air will reduce the effectiveness of this product, it is important to cover any chemical mixing tank and minimize the use of the agitator when using this product.

### **AVAILABILITY**

20 Litre Pail

205 Litre Drum

### **HANDLING PRECAUTIONS**

Wear the appropriate safety equipment before handling any chemicals. For further information, please refer to the Material Safety Data Sheet.

### **TERMS OF SALE**

To the best of our knowledge the information contained herein is accurate and true. Any recommendations or suggestions are made without warranty or liability on our part since the conditions of use are beyond our control.

*For further information on this product, please contact our office or your service representative .*